

Walplast®

# BUILDWELL

READY-MIX MORTAR



## Highlights

- ✓ Compact Plaster, Reduce Void Gaps
- ✓ Negligible Silt Content
- ✓ Smooth Plastering
- ✓ Polymers Already Added To Enhance Overall Durability

## HOW TO APPLY



The substrate needs to be cleaned and made free from grease and loose particles. Then dampen the surface with clean water.



Add Ready Mix Mortar to Potable water & mix well for 5-10mins. (Recommended mix 15-17% water)



Allow Mixture to stand for 5 mins. & then Re-mix again for 2 mins.



Apply plaster to the substrate, using some pressure while finishing with a steel trowel or wooden float to ensure optimum bonding.



Apply aluminum level patty from bottom to top direction followed by left to right & right to left direction to level the plaster.



Plain plaster wall, ready for wall putty Application.



Post 24 hours curing is recommended for 7 days.

## KEY FEATURES

- Reduces rebounding loss
- Highly durable plaster
- Cuts repair & maintenance cost
- Time-saving
- Cost-effective
- Excellent work ability & Substrates
- Pre-mixed, only water to be added
- RMM can be used for interior as well as exterior walls

## TECHNICAL INFORMATION

TEST	TEST METHOD	SPECIFICATION	RESULTS
Water Demand	IS-4031(Part-4)1988	15-25%	16
Pot Life	Internal	>90 Minutes	130
Setting Time: Initial	IS:4031 (part-5) :1988	>30 min	200
Setting Time: Final		<=600 min	210

## COVERAGE

BuildWell Ready-Mix Mortar's approx coverage per 40 kg bag is as under:

- 10-12 mm plaster on light weight blocks is 17-18 sq. ft.
- 10-12 mm on brick wall 14-15 sq. ft.
- 18 mm on light weight blocks is 11 sq. ft.
- 25 mm on brick wall 7-7.5 sq. ft.
- 10 mm on RCC 20-22 sq. ft.
- Coverages depend on quality and nature of substrates hence is indication.
- Plaster >More than 10-12 mm thickness must be in 2 coats.

RMM

STORAGE



**Walplast Products Pvt. Ltd.** ISO 9001 : 2015 Certified Company

**Corporate Office:** Rainbow Building, Plot No. 13, Sector - 24, Mumbai Pune Highway Service Road, Turbhe, Navi Mumbai - 400 705, Maharashtra, India. **Tel no.:** 022-41418282. **Enquiry No.:** 1800 3000 6650

**Email:** sales@walplast.com, customercare@walplast.com / **For more details visit us at:** [www.walplast.com](http://www.walplast.com)

**Disclaimer:** The product information and application details given by the company and its agents has been provided in good faith and meant to serve only as a general guideline during usage. Users are advised to carry out test and take trials to ensure on the suitability of the products meeting their requirement prior to the full scale usage of our products. Once the correct identification of the problems, quality or other materials used and the on-site workmanship are factors beyond our control, there is no guarantee whatsoever as to the result obtained. The company does not assume any liability for unsatisfactory results arising from the use of our products.